



### Installation Method



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Natural Woodgrains **Colour** A00207 Washed Wheat

### Product Specifications

Product Number	A002
Product Construction	High Performance Luxury Vinyl Tile
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	(EN ISO 23997) 6700 g/m <sup>2</sup>
Size – Packaging	25 x 100 cm – 2.5 m <sup>2</sup> Box
Backing	Sound Choice™ Acoustic Backing

### Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial	
CE Declaration Of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
Castor Chair Rating	(ISO 4918 / EN425) Pass	
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value 59.2	LRV – Y value 27.3
Dimensional Stability	(ISO 23999) ≤ 0.25%	
Curling	(ISO 23999) ≤ 2 mm	
Flexibility	(EN ISO 24344) Method A - Pass.	
Abrasion Resistance	(EN 660-2) Group T	
Residual Indentation	mm(EN ISO 24343-1) ≤ 0.2	
Determination of Anti-Slip	(DIN 51130) R9	
Chemical Resistance	(EN ISO 26987) Very Good	
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	16 dB	

### Environmental Specifications

Indoor Air Quality	French A+ <a href="#">Indoor Air Comfort GOLD®</a>
Potential Green Building Contribution	
Environmental Product Declaration	<a href="#">MR-ULE-EPD-INF-20170001-EN</a>
Carbon Footprint	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	12.4 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	1.4 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	5.47 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	0.5 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	19.77 kg CO <sub>2</sub> eq./m <sup>2</sup>
Installation Impacts	
TacTiles®	Can be installed with glue-free TacTiles® for PVC up to 50 m <sup>2</sup> , for virtually zero VOCs.
End of Life Options	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

### Technical Information

Installation	<a href="#">See recommended LVT installation guidelines</a>
Maintenance	<a href="#">See recommended LVT maintenance guidelines</a>
Warranty	15 years

### Performance Qualifications



16 dB ≥7

### Certifications

**CE**

---

17

---

Interface European Manufacturing B.V.  
 Industrielaan 15  
 3925 BD  
 Scherpenzeel  
 The Netherlands

---

**DOP PBRG - AHCK3R**

---

EN 14041:2004  
 Notified Body - 0321

---

Resilient floor covering for internal use.

Classification	Class 33/42 (EN ISO 10874)
Reaction to fire	Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance	Class DS (See EN 14041, clause 4.5)
Formaldehyde	E1 (see EN 14041, clause 4.3)
Anti-static	0.2kV (See EN14041, clause 4.6.1)

---

[www.interface.com/lv-emea](http://www.interface.com/lv-emea)

