



Installation Method



Herringbone Ashlar

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Textured Woodgrains **Colour** A00404 Distressed Black Walnut

Product Specifications

| | |
|----------------------|---|
| Product Number | A004 |
| Product Construction | High Performance Luxury Vinyl Tile |
| Finish | Ceramor™ - UV Stabilised Ceramic Bead Coating |
| Wear Layer Thickness | (EN ISO 24340) 0.55 mm |
| Total Thickness | (EN ISO 24346) 4.5 mm |
| Total Weight | (EN ISO 23997) 6700 g/m ² |
| Size – Packaging | 25 x 100 cm – 2.5 m ² Box |
| Backing | Sound Choice™ Acoustic Backing |

Performance Specifications

| | | |
|---|--|-----------------------|
| Wear Classification | EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial | |
| CE Declaration Of Performance | DOP PBRG-AHCK3R | |
| Castor Chair Rating | (ISO 4918 / EN425) Pass | |
| Flammability | (EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1) | |
| Light Fastness | ≥7 (ISO 105-B02) | |
| Light Reflectance Value (LRV) | LRV – L value 38.7 | LRV – Y value 10.5 |
| Dimensional Stability | (ISO 23999) ≤ 0.25% | |
| Curling | (ISO 23999) ≤ 2 mm | |
| Flexibility | (EN ISO 24344) Method A - Pass. | |
| Abrasion Resistance | (EN 660-2) Group T | |
| Residual Indentation | mm(EN ISO 24343-1) ≤ 0.2 | |
| Determination of Anti-Slip | (DIN 51130) R9 | |
| Chemical Resistance | (EN ISO 26987) Very Good | |
| Impact Sound Insulation ΔL _w EN ISO 10140-3 | 16 dB | |

Environmental Specifications

| | |
|---------------------------------------|--|
| Indoor Air Quality | French A+ Indoor Air Comfort GOLD® |
| Potential Green Building Contribution | |
| Environmental Product Declaration | MR-ULE-EPD-INF-20170001-EN |
| Carbon Footprint | |
| Full Life Cycle Carbon Footprint | According to EPD or EPD calculation method |
| Raw Materials and Production | 12.4 kg CO ₂ eq./m ² |
| Delivery and Installation | 1.4 kg CO ₂ eq./m ² |
| Use (10 Years) | 5.47 kg CO ₂ eq./m ² |
| End of Life (Waste to Energy) | 0.5 kg CO ₂ eq./m ² |
| Total (10 Years Lifetime) | 19.77 kg CO ₂ eq./m ² |
| Installation Impacts | |
| TacTiles® | Can be installed with glue-free TacTiles® for PVC up to 50 m ² , for virtually zero VOCs. |
| End of Life Options | |
| ReUse | Can be cleaned and reused in a non-critical location to extend its useful life. |
| Fully Recyclable | Can be recycled into carpet tile backing. |
| Material Composition | Free of Ortho Phthalates |

Technical Information

| | |
|--------------|---|
| Installation | See recommended LVT installation guidelines |
| Maintenance | See recommended LVT maintenance guidelines |
| Warranty | 15 years |

Performance Qualifications



16 dB ≥7

Certifications

CE

17

Interface European Manufacturing B.V.
Industrielaan 15
3925 BD
Scherpenzeel
The Netherlands

DOP PBRG - AHCK3R

EN 14041:2004
Notified Body - 0321

Resilient floor covering for internal use.

| | |
|------------------|---|
| Classification | Class 33/42 (EN ISO 10874) |
| Reaction to fire | Class Bfl-s1 (see EN 14041, clause 4.1) |
| Slip resistance | Class DS (See EN 14041, clause 4.5) |
| Formaldehyde | E1 (see EN 14041, clause 4.3) |
| Anti-static | 0.2kV (See EN14041, clause 4.6.1) |

www.interface.com/lv-emea

