



### Installation Method



Monolithic

Quarter Turn

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Collection** Urban Retreat **Product** UR202 **Colour** 326986 Sage

### Product Specifications

Product Number	7136
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®
Size – Packaging	50 x 50 cm – 4 m² Box
Pile Yarn Weight	886 g/m² ± 5%
Total Weight	4539 g/m² ± 5%
Pile Height	3.8 mm +15% / - 10%
Total Thickness	7.5 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m²	197,000/m² ±5%

### Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	45.1			14.6		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	27 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.00	0.06	0.12	0.29	0.38	0.51

### Environmental Specifications

Total Recycled Content	62.22%				
Pre-Consumer (Total)	52.52%				
Post-Consumer (Total)	9.7%				
Yarn Recycled Content	100%				
Pre-Consumer (Yarn)	50%				
Post-Consumer (Yarn)	50%				
Indoor Air Quality	GUT Prodis ID CACC31EC				
	<a href="#">Danish Indoor Climate</a>				
	French A+				
	<a href="#">GLP 9819</a>				
Potential Green Building Contribution	<a href="#">GUI Standard</a>				
	BREEAM (UK/International)				
	<a href="#">View potential BREEAM contribution</a>				
	BRE Green Guide Ratings				
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)
A+	A	A+	A+	A+	A+
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>				
HQE (France)	<a href="#">View Potential HQE Contribution</a>				
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>				
Environmental Product Declaration	<a href="#">wc_eu-epd-int-20180094-ur202-cbc1-en</a>				

## Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	5.8 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.63 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.21 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	6.74 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	20.87 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

## Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:
	Quarter turn – 3-4%
	Monolithic – 3-4%
	For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

## End of Life Options

ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

## Technical Information

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

## Performance Qualifications



## Certifications

