



## Installation Method



Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Collection** Composure **Product** Composure Edge **Colour** 4274003 Olive/Seclusion

## Product Specifications

Product Number	4274
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®, SONE®, CircuitBac Green
Size – Packaging	50 x 50 cm – 4 m² Box
Pile Yarn Weight	665 g/m² ± 5%
Total Weight	4326 g/m² ± 5%
Pile Height	3 mm +15% / - 10%
Total Thickness	6.3 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/12 - 47.2
Tufts per m²	188,800/m² ±5%

## Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
	Bfl-s1 on request					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	44.2			14		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	25 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.05	0.08	0.22	0.34	0.44

## Environmental Specifications

Total Recycled Content	50.8%				
Pre-Consumer (Total)	49.3%				
Post-Consumer (Total)	1.5%				
Yarn Recycled Content	34.5%				
Pre-Consumer (Yarn)	24.5%				
Post-Consumer (Yarn)	10%				
Indoor Air Quality	GUT Prodis ID C46D295E <a href="#">GLP 9819</a> Compliant with <a href="#">LEED EQ 4.3 credit</a> French A+ <a href="#">Danish Indoor Climate</a> <a href="#">GUI Standard</a>				
Potential Green Building Contribution					
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>				
BRE Green Guide Ratings					
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>				
HQE (France)	<a href="#">View Potential HQE Contribution</a>				
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>				
Environmental Product Declaration	<a href="#">wc_eu-epd-int-20180117-composureedge-cbc1-en</a>				

## Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	10.1 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.69 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.43 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	5.1 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	19.32 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

## Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Non-directional – 1-2%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

## End of Life Options

Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

## Technical Information

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

## Performance Qualifications



## Certifications

