FELTOUCH

V PLATE Product Code: PT110V & PT100V

Plate's are the source of inspiration for Plativity Collection with an endless ideas. They offer tailor made acoustic solutions by various thicknesses and dimensions. It allows unique and customizable designs by CNC cutting. Semirigid Plate sheets are lightweight and easy to install.

Specification

Composition: 100 % polyester (recycled PET appx. 50 %)

Material Weight: 6mm: 1300g/m² (+/- 5 %)

Material Thickness: 6mm Natural & Mandarin colors (+/- 10 %)

Product Weight:

Performance

Acoustic Rates:
NRC (EN-11654) with no air gap

• Fire Rates: B, S1, d0 (EN-13501)

Light fastness: 6+ (ISO-105 B02)

MAS Certified Green - CDPH Standard Method v1.2
 Low VOC / Eligible for LEED v4

Health: 99.9 % Antibacterial (ISO-20743)
 Formaldehyde-free (ISO-14184)

 Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)

• Thearmal insulating: 0,040 W/mK

Key Features & Benefits

- Available in 6 natural composite colours & 25 Mandarin colours
- Highly durable providing long-term stability and performance
- Safe, non-toxic, non-irritant & without red list chemical binders
- Recycled and recyclable

Care

- Easy to clean with a damp cloth or vacuum cleaner
- Indoor use only

Installation


Prior to installation, walls and surfaces must be clean, dust free and void of any defects or imperfections. Contact-type adhesive for applying plate on surfaces such as plasterboard, concrete, block, plywood, mdf and particleboard. Feltouch reccommends Pattex PL600 & Liquid Nails LN-2000 or equivalent adhesive with glu gun.

Dimensions (mm):

PT110V

L: 1800mm W: 1400mm


Thickness: 6mm/12mm



PT100V

L: 2400mm W: 1200mm

Thickness: 6mm/12mm




FELTOUCH


V PLATE

Product Code: PT110V & PT100V

Thickness: 6mm Natural Felt



Thickness: 6mm Mandarin Felt (Natural + Mandarin (finish layer))



Thickness: 12mm Natural Felt

