FELTOUCH



RATE BAFFLE UNIT 240

Baffle models of Plativity Collection are simple, elegant and one of the most dynamic modular acoustic ceiling systems. Easy to install, lightweight and can be installed quickly to transform large volumes to linear ceiling systems. Baffle delivers tailor made acoustic solutions with cut out 12mm thickness of Plate sheets that offers adjustable gap between felt baffles and various dimensions. On request it allows various thickness and customizable designs.

Specification

- Composition: 100 % polyester (recycled PET appx. 50 %)
- Material Weight: 12mm: 2600g/m² (+/- 5 %), 12mm: 3000g/m² (+/- 5 %)
- Material Thickness: 12mm Natural & Mandarin colors (+/- 10 %)
- Panel Weight: 240*300cm h:12cm 15 kg / per pcs. (+/-5 %)

Performance


- Acoustic Rates: 2,16 NRC (EN-11654)
- Fire Rates: B, S1, d0 (EN-13501)
- Light fastness: 6+ (ISO-105 B02)
- MAS Certified Green CDPH Standard Method v1.2 Low VOC / Eligible for LEED v4
- Health: 99.9 % Antibacterial (ISO-20743) Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thearmal insulating: 0,040 W/mK

Key Features & Benefits

- Available in 6 natural composite colours & 25 Mandarin colours
- Highly durable providing long-term stability and performance
- Safe, non-toxic, non-irritant & without red list chemical binders
- Recycled and recyclable

Care

- Easy to clean with a damp cloth or vacuum cleaner
- Indoor use only







Product Code: PT332

Dimensions(mm):

L: 3000mm W: 2400mm h: 150mm CTC: 150mm





FELTOUCH

RATE BAFFLE UNIT 240

