



## Installation Method



Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Collection** Human Connections **Product** Sett In Stone **Colour** 8342003 Flint

## Product Specifications

Product Number	8342
Product Construction	Tapestry Tufted Patterned Structured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
Size – Packaging	50 x 50 cm – 4 m² Box
Pile Yarn Weight	746 g/m² ± 5%
Total Weight	4387 g/m² ± 5%
Pile Height	4 mm +15% / - 10%
Total Thickness	7.1 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m²	139,870/m² ±5%

## Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
	Bfl-s1 on request					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	39.7			11.1		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	24 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.02	0.04	0.07	0.27	0.33	0.48

## Environmental Specifications

Total Recycled Content	54.73%				
Pre-Consumer (Total)	46.22%				
Post-Consumer (Total)	8.51%				
Yarn Recycled Content	100%				
Pre-Consumer (Yarn)	50%				
Post-Consumer (Yarn)	50%				
Indoor Air Quality	GUT Prodis ID PENDING <a href="#">GLP 9819</a> <a href="#">Compliant with LEED EQ 4.3 credit</a> French A+ <a href="#">Danish Indoor Climate</a> <a href="#">GUI Standard</a>				
Potential Green Building Contribution					
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>				
BRE Green Guide Ratings					
Commercial	Domestic	Education	Health	Retail <small>(Fashion)</small>	Retail <small>(Durability)</small>
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>				
HQE (France)	<a href="#">View Potential HQE Contribution</a>				
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>				
Environmental Product Declaration	<a href="#">wc_eu-epd-int-20180094-settinstone-cbc1-en</a>				

## Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	5.32 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.6 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.21 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	6.42 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	15.55 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

## Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Non-directional – 1-2%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

## End of Life Options

Waste to Energy	Can be incinerated in appropriate waste to energy plant.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.

## Technical Information

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

## Performance Qualifications



## Certifications

